

ORDERING INFORMATION

Example: a 10 series light dependent relay with 1 NO - 12 A contact and screw terminal connections, with 230 V AC supply.

1 0 . 4 1 . 8 . 2 3 0 . 0 0 0 0

Series _____

Type _____
 3 = Pole mount - 2 NO
 4 = Pole mount - 1 NO

No. of poles _____
 1 = Single phase switch 1 NO, 12 A
 2 = Double phase switch 2 NO, 16 A

Supply voltage
 230 = 230 V

Supply version
 8 = AC (50/60 Hz)

TECHNICAL DATA

INSULATION		10.32	10.41		
DIELECTRIC STRENGTH - between open contacts	V AC	1,000	1,000		
OTHER DATA		10.32	10.41		
CABLE GRIP	Ø mm	(8.9...13)	(8.9...13)		
PRESET THRESHOLD	lx	5 switch ON / 20 switch OFF	3 switch ON / 8 switch OFF		
MAX WIRE SIZE		solid cable	solid cable	stranded cable	
	mm ²	1x6 / 2x4	1x6 / 2x2.5	1x6 / 2x4	1x6 / 2x2.5
	AWG	1x10 / 2x12	1x10 / 2x14	1x10 / 2x12	1x10 / 2x14
SCREW TORQUE	Nm	1.2	1.2		

WIRING DIAGRAMS

